

Go Pro 35 PF | 9W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included





Mounting Remote

LED Power Watts 7.5W

System Power Watts 8.6W

Operating Voltage V_{in} 220-240 Vac

Power Factor p.f. > 0.95



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 9Vdc/700mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTDM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Go Pro 35 PF	9W	WW27K	CRI80	24°(MD)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL	
Go Pro 35 PF	9W	697	81	2700K	WW27K	CRI80	24°(MD)	White SWH	Non Dimmable On/Off
		722	84	3000K	WW30K	CRI90	36°(WD)	Black SBL	Phase Dimmable PDIM
		757	88	4000K	NW40K		52°(VWD)		Dali Dimmable DDIM
		783	91	5700K	CW57K			Bluetooth Dimmable BTDM	
					2700K-5700K	TW			Casambi CBTM
					Warm to Dim	W2D			
Go Pro 35 PF	9W			WW27K	CRI80	24°(MD)	SWH	On/Off	