

# Go Pro 50 TL | 15W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included






Mounting Remote

LED Power Watts 12.4W

System Power Watts 14.2W

Operating Voltage  $V_{in}$  220-240 Vac

Power Factor p.f. > 0.95



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/350mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTDM,CASAMBI,Non Dimmable

## Ordering Details

| Code Example: | Name         | Watt | CCT   | CRI   | Angle   | Finish | Control |
|---------------|--------------|------|-------|-------|---------|--------|---------|
|               | Go Pro 50 TL | 15W  | WW27K | CRI80 | 20°(SS) | SWH    | On/Off  |

Select one from each column with highlighted values to create the ordering code

| NAME         | WATT | LUMEN | EFFICACY | CCT   | CRI         | ANGLE   | FINISH   | CONTROL   |                        |              |
|--------------|------|-------|----------|-------|-------------|---------|----------|-----------|------------------------|--------------|
| Go Pro 50 TL | 15W  | 1392  | 98       | 2700K | WW27K       | CRI80   | 20°(SS)  | White SWH | Non Dimmable On/Off    |              |
|              |      | 1434  | 101      | 3000K | WW30K       | CRI90   | 30°(MD)  | Black SBL | Phase Dimmable PDIM    |              |
|              |      | 1505  | 106      | 4000K | NW40K       |         | 35°(WD)  |           | Dali Dimmable DDIM     |              |
|              |      | 1534  | 108      | 5700K | CW57K       |         | 49°(VWD) |           | Bluetooth Dimmable BTM |              |
|              |      |       |          |       | 2700K-5700K | TW      |          |           |                        | Casambi CBTM |
|              |      |       |          |       | Warm to Dim | W2D     |          |           |                        |              |
| Go Pro 50 TL | 15W  |       |          | WW27K | CRI80       | 20°(SS) | SWH      | On/Off    |                        |              |