

Go Pro 50 P | 24W

Product Reference

Environment Indoor
Installation Ceiling Suspended

Construction & Materials

Housing Die Cast Aluminium
Primary Lens PMMA
Primary Reflector -
Secondary Reflector Anodised
Body Finish White,Black,Custom
Diffuser -
Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium
Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed
Tilt No
Swivel No

Electrical System


Driven with Constant Current Driver
Input Voltage/Hz 220V- 240V/50-60Hz
Control Gear Included
Mounting Integral
LED Power Watts 20.2W
System Power Watts 23.2W
Operating Voltage Vin 220-240 Vac
Power Factor p.f. > 0.95

Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Go Pro 50 P	24W	WW27K	CRI80	24°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL	
Go Pro 50 P	24W	2204	95	2700K	WW27K	CRI80	24°(SS)	White SWH	Non Dimmable On/Off
		2274	98	3000K	WW30K	CRI90	32°(MD)	Black SBL	
		2390	103	4000K	NW40K		36°(WD)	Custom CSM	
		2436	105	5700K	CW57K		46°(VWD)		
Go Pro 50 P	24W			WW27K	CRI80	24°(SS)	SWH	On/Off	



Light Distribution



LED Technology

Binning 3 Step MacAdam
LED Life Time @ L70/B10 >50000 hours
Colour Rendering (CRI) CRI80,CRI90
Led Type COB
LED Fitted CREE COB LED 36Vdc/600mA

Controls

Standard Switchable On/Off
Optional Non Dimmable