

## Barrel S | 15W

### Product Reference

Environment Indoor

Installation Ceiling Surface

### Construction & Materials

Housing Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal

Antiglare Baffle -

### Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

### Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

### Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 12.4W

System Power Watts 14.2W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

### Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Barrel S</b>	<b>15W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>84°</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL		
<b>Barrel S</b>	<b>15W</b>	1448	102	2700K	<b>WW27K</b>	84°	White	<b>SWH</b>	Non Dimmable	<b>On/Off</b>
		1491	105	3000K	<b>WW30K</b>		Black	<b>SBL</b>	Phase Dimmable	<b>PDIM</b>
		1576	111	4000K	<b>NW40K</b>		Custom	<b>CSM</b>	Dali Dimmable	<b>DDIM</b>
		1619	114	5700K	<b>CW57K</b>					
				2700K-5700K	<b>TW</b>					
<b>Barrel S</b>	<b>15W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>84°</b>	<b>SWH</b>	<b>On/Off</b>		



### Light Distribution



### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 33V-36Vdc/350mA

### Controls

Standard Switchable On/Off

Optional PDIM,DDIM,Non Dimmable