

# Halo | 8W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Spun Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 6.6W


System Power Watts 7.6W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 32V-36Vdc/200mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Halo</b>	<b>8W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>88°</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>Halo</b>	<b>8W</b>	547	72	2700K	<b>WW27K</b>	<b>88°</b>	White	Non Dimmable
		562	74	3000K	<b>WW30K</b>		Black	Phase Dimmable
		593	78	4000K	<b>NW40K</b>		Custom	Dali Dimmable
		608	80	5700K	<b>CW57K</b>		Bluetooth Dimmable	BTTM
				2700K-5700K	<b>TW</b>		Casambi	CBTM
<b>Halo</b>	<b>8W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>88°</b>	<b>SWH</b>	<b>On/Off</b>

