

Halo | 14W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Spun Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included



Mounting Remote

LED Power Watts 12.0W

System Power Watts 13.8W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 32V-36Vdc/350mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Halo	14W	WW27K	CRI80	88°	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Halo	14W	897	65	2700K	WW27K	88°	White	Non Dimmable
		925	67	3000K	WW30K		Black	Phase Dimmable
		966	70	4000K	NW40K		Custom	Dali Dimmable
		994	72	5700K	CW57K		Bluetooth Dimmable	BTTM
				2700K-5700K	TW		Casambi	CBTM
Halo	14W			WW27K	CRI80	88°	SWH	On/Off