

ABBY LIGHTING

220V 240V 50/60Hz | CRI 80 | IP20 | L80B10 >50,000h | MacAdam Step 3

Optional: Bluetooth | Dimmable | CRI 90

Nova 14 | 36W





Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing CRCA

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material -

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote


LED Power Watts 30.0W

System Power Watts 34.5W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95

Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 26V-32Vdc/1000mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Nova 14	**36W**	**WW27K**	**CRI80**	**95°**	**SWH**	**On/Off**

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Nova 14	**36W**	3209	93	2700K	**WW27K**	**CRI80**	95°	White	**SWH**	Non Dimmable	**On/Off**
		3312	96	3000K	**WW30K**	CRI90				Phase Dimmable	**PDIM**
		3519	102	4000K	**NW40K**					Dali Dimmable	**DDIM**
		3623	105	5700K	**CW57K**					Bluetooth Dimmable	**BTTM**
										Casambi	**CBTM**
Nova 14	**36W**			**WW27K**		**CRI80**	**95°**	**SWH**		**On/Off**	