

Nova 22 | 42W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing CRCA

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material -

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included



Mounting Remote

LED Power Watts 36.0W


System Power Watts 41.4W

Operating Voltage V_{in} 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 30V-38Vdc/1000mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Nova 22	42W	WW27K	CRI80	105°	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Nova 22	42W	4430	107	2700K	WW27K	105°	White SWH	Non Dimmable On/Off
		4554	110	3000K	WW30K			Dali Dimmable DDIM
		4844	117	4000K	NW40K			Bluetooth Dimmable BTTM
		4968	120	5700K	CW57K			Casambi CBTM
Nova 22	42W			WW27K	CRI80	105°	SWH	On/Off

