

Nova 22 | 42W

Product Reference

Environment Indoor
Installation Ceiling Recess

Construction & Materials

Housing CRCA
Primary Lens -
Primary Reflector -
Secondary Reflector -
Body Finish White
Diffuser Premium high-transmission opal
Antiglare Baffle -

Thermal Management

Heat Sink Material -
Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse
Tilt No
Swivel No

Electrical System


Driven with Constant Current Driver
Input Voltage/Hz 220V- 240V/50-60Hz
Control Gear Included
Mounting Remote
LED Power Watts 36.0W
System Power Watts 41.4W
Operating Voltage Vin 220-240 Vac
Power Factor p.f. > 0.95

Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Nova 22	42W	WW27K	CRI80	105°	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL		
Nova 22	42W	4430	107	2700K	WW27K	105°	White	SWH	Non Dimmable	On/Off
		4554	110	3000K	WW30K			CRI90	Dali Dimmable	DDIM
		4844	117	4000K	NW40K			Bluetooth Dimmable	BTTM	
		4968	120	5700K	CW57K			Casambi	CBTM	
Nova 22	42W			WW27K	CRI80	105°	SWH	On/Off		



Light Distribution



LED Technology

Binning 3 Step MacAdam
LED Life Time @ L70/B10 >50000 hours
Colour Rendering (CRI) CRI80,CRI90
Led Type SMD mid power
LED Fitted Samsung Mid power LED array 30V-38Vdc/1000mA

Controls

Standard Switchable On/Off
Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable