

Croc | 5W

Product Reference

Environment Outdoor

Installation Floor Surface,Wall Surface,Wall Surface

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish Black,Grey

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable

Tilt Yes

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 3.4W

System Power Watts 4.3W

Operating Voltage Vin 220-240 Vac



Power Factor p.f. > 0.5

Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Croc	5W	WW27K	CRI80	16°(SS)	SBL	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Croc	5W	357	83	2700K	WW27K	CRI80	16°(SS)	Black	SBL	Non Dimmable	On/Off
		378	88	3000K	WW30K	CRI90	22°(MD)	Grey	GGT		
		400	93	4000K	NW40K		32°(WD)				
		413	96	5700K	CW57K						
Croc	5W			WW27K		CRI80	16°(SS)	SBL		On/Off	



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 9Vdc/350mA

Controls

Standard Switchable On/Off

Optional Non Dimmable