

Hugo 25 | 8W

Product Reference

Environment Outdoor

Installation Floor Surface

Construction & Materials

Housing Die Cast Aluminium, Extruded Aluminium

Primary Lens Polycarbonate

Primary Reflector -

Secondary Reflector -

Body Finish Black, Grey

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 7.5W


System Power Watts 8.6W

Operating Voltage V_{in} 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80, CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 32V-36Vdc/200mA

Controls

Standard Switchable On/Off

Optional Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Hugo 25	8W	WW27K	CRI80	120°	SBL	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL		
Hugo 25	8W	490	57	2700K	WW27K	120°	Black	Non Dimmable		
		507	59	3000K	WW30K		CRI80		SBL	
		533	62	4000K	NW40K		CRI90		Grey	GGT
		542	63	5700K	CW57K					
Hugo 25	8W			WW27K	CRI80	120°	SBL	On/Off		