

Wally | 6W

Product Reference

Environment Outdoor

Installation Wall Surface,Wall Surface

Construction & Materials

Housing Die Cast Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Grey

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 5.1W

System Power Watts 5.9W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Wally	6W	WW27K	CRI80		SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Wally	6W	271	46	2700K	WW27K	CRI80		White	SWH	Non Dimmable	on/off
		283	48	3000K	WW30K	CRI90		Black	SBL		
		295	50	4000K	NW40K			Grey	GGT		
		301	51	5700K	CW57K						
Wally	6W			WW27K		CRI80		SWH		On/Off	



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 32-36Vdc/150mA

Controls

Standard Switchable On/Off

Optional Non Dimmable