
ABBY LIGHTING

220V 240V 50/60Hz | CRI 80 | IP20 | L80B10 >50,000h | MacAdam Step 3 | Swivel | Tilt

Optional: CRI 90

Spotboy Pro ITA 75 | 20W





Product Reference

Environment Indoor

Installation Track Mounted

Construction & Materials

Housing Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish White,Black

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral


LED Power Watts 17.5W

System Power Watts 20.1W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95

Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 33V-36Vdc/500mA

Controls

Standard Switchable On/Off

Optional Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Spotboy Pro ITA 75	**20W**	**WW27K**	**CRI80**	**20°(SS)**	**SWH**	**On/Off**

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Spotboy Pro ITA 75	**20W**	1849	92	2700K	**WW27K**	**CRI80**	20°(SS)	White	**SWH**	Non Dimmable	**On/Off**
		1910	95	3000K	**WW30K**	CRI90	37°(MD)	Black	**SBL**		
		2010	100	4000K	**NW40K**		54°(WD)				
		2050	102	5700K	**CW57K**						
Spotboy Pro ITA 75	**20W**			**WW27K**		**CRI80**	**20°(SS)**	**SWH**		**On/Off**	

Abby Lighting & Switchgear Limited 802 A, Fortune Terraces, New Link Road, Opp City Mall, Andheri West, Mumbai - 400053, India.
frontdesk@abbylighting.com, +91 7304623220
www.abbylighting.com

Abby reserves the right to discontinue any product from its collection at any time whatsover and without prior notice