

# Tango 75 | 22W

## Product Reference

Environment Indoor

Installation Track Mounted

## Construction & Materials

Housing Extruded and Die Cast Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 18.9W

System Power Watts 21.7W

 Operating Voltage  $V_{in}$  220-240 Vac





Power Factor p.f. &gt; 0.95

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Tango 75</b>	<b>22W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>20°(SS)</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL	
<b>Tango 75</b>	<b>22W</b>	1671	77	2700K	<b>WW27K</b>	<b>CRI80</b>	20°(SS)	White <b>SWH</b> Non Dimmable <b>On/Off</b>	
		1779	82	3000K	<b>WW30K</b>	CRI90	25°(MD)	Black <b>SBL</b> Phase Dimmable <b>PDIM</b>	
		1931	89	4000K	<b>NW40K</b>		35°(WD)	Dali Dimmable <b>DDIM</b>	
		1975	91	5700K	<b>CW57K</b>			Casambi <b>CBTM</b>	
					2700K-5700K	<b>TW</b>			
					Warm to Dim	<b>W2D</b>			
<b>Tango 75</b>	<b>22W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>20°(SS)</b>	<b>SWH</b>	<b>On/off</b>	



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 &gt;50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/500mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable