

Dark Magic Wash 48V 56 | 14.7W

Product Reference

Environment Indoor

Installation Track Mounted

Construction & Materials

Housing Die Cast Aluminium

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector Black Raster - ABS

Body Finish Black

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable

Tilt Yes

Swivel No

Electrical System

Driven with Constant Voltage Driver

Input Voltage/Hz 48V

Control Gear Included


Mounting Remote

LED Power Watts 14.6W


System Power Watts -

Operating Voltage Vin 48V

Power Factor p.f. -



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD high power

LED Fitted Cree 3030 LED 39V-42Vdc/350mA

Controls

Standard Switchable On/Off

Optional DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Dark Magic Wash 48V 56	14.7W	WW27K	CRI80	29°(MD)	SBL	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH	CONTROL	
Dark Magic Wash 48V 56	14.7W	1664	114	2700K	WW27K	CRI80	29°(MD)	Black SBL	Non Dimmable	On/Off
		1723	118	3000K	WW30K	CRI90	66°(VWD)		Dali Dimmable	DDIM
		1796	123	4000K	NW40K				Bluetooth Dimmable	BTTM
		1840	126	5700K	CW57K				Casambi	CBTM
				2700K-5700K	TW					
Dark Magic Wash 48V 56	14.7W			WW27K		CRI80	29°(MD)	SBL	On/Off	

Abby reserves the right to discontinue any product from its collection at any time whatsoever and without prior notice

frontdesk@abbylighting.com, +91 9833645212

www.abbylighting.com