

Ovo 48V | 10.8W

Product Reference

Environment Indoor

Installation Track Mounted

Construction & Materials

Housing Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Voltage Driver

Input Voltage/Hz 48V

Control Gear Included


Mounting Remote

LED Power Watts 10.4W


System Power Watts -

Operating Voltage Vin 48V

Power Factor p.f. -



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 33V-36Vdc/300mA

Controls

Standard Switchable On/Off

Optional DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Ovo 48V	10.8W	WW27K	CRI80	32°(MD)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL	
Ovo 48V	10.8W	957	92	2700K	WW27K	CRI80	32°(MD)	White SWH	Non Dimmable On/Off
		988	95	3000K	WW30K	CRI90	42°(WD)	Black SBL	Dali Dimmable DDIM
		1040	100	4000K	NW40K				Bluetooth Dimmable BTTM
		1061	102	5700K	CW57K				Casambi CBTM
					Warm to Dim W2D				
Ovo 48V	10.8W			WW27K	CRI80	32°(MD)	SWH	On/Off	