

# Spot On Framer ITA 85

## Narrow Beam | 28W

### Product Reference

Environment Indoor  
Installation Track Mounted

### Construction & Materials

Housing Aluminium  
Primary Lens PMMA  
Primary Reflector -  
Secondary Reflector -  
Body Finish White,Black  
Diffuser -  
Antiglare Baffle -

### Thermal Management




Heat Sink Material Aluminium  
Cooling Technique Passive Cooling

### Optical System

Beam Direction Adjustable  
Tilt Yes  
Swivel Yes

### Electrical System

Driven with Constant Current Driver  
Input Voltage/Hz 220V- 240V/50-60Hz  
Control Gear Included  
Mounting Remote  
LED Power Watts 24.0W  
System Power Watts 27.6W  
Operating Voltage Vin 220-240 Vac  
Power Factor p.f. > 0.95



### LED Technology

Binning 3 Step MacAdam  
LED Life Time @ L70/B10 >50000 hours  
Colour Rendering (CRI) CRI80,CRI90  
Led Type COB  
LED Fitted Cree COB LED 36Vdc/700mA

### Controls

Standard Switchable On/Off  
Optional Non Dimmable

### Ordering Details

| Code Example: | Name                                     | Watt       | CCT          | CRI          | Angle          | Finish     | Control       |
|---------------|--|------------|--------------|--------------|----------------|------------|---------------|
|               | <b>Spot On Framer ITA 85 Narrow Beam</b> | <b>28W</b> | <b>WW27K</b> | <b>CRI80</b> | <b>24°-34°</b> | <b>SWH</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME                                     | WATT       | LUMEN | EFFICACY | CCT                | CRI          | ANGLE          | FINISH           | CONTROL                    |
|--|------------|-------|----------|--------------------|--------------|----------------|------------------|----------------------------|
| <b>Spot On Framer ITA 85 Narrow Beam</b> | <b>28W</b> | 1132  | 41       | 2700K <b>WW27K</b> | <b>CRI80</b> | 24°-34°        | White <b>SWH</b> | Non Dimmable <b>On/Off</b> |
|  |            | 1159  | 42       | 3000K <b>WW30K</b> | CRI90        |                | Black <b>SBL</b> |                            |
|  |            | 1214  | 44       | 4000K <b>NW40K</b> |              |                |                  |                            |
|  |            | 1242  | 45       | 5700K <b>CW57K</b> |              |                |                  |                            |
| <b>Spot On Framer ITA 85 Narrow Beam</b> | <b>28W</b> |       |          | <b>WW27K</b>       | <b>CRI80</b> | <b>24°-34°</b> | <b>SWH</b>       | <b>On/Off</b>              |