

Spot On Framer ITA 85

Wide Beam | 28W

Product Reference

Environment Indoor
 Installation Track Mounted

Construction & Materials

Housing Aluminium
 Primary Lens PMMA
 Primary Reflector -
 Secondary Reflector -
 Body Finish Black
 Diffuser -
 Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium
 Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable
 Tilt Yes
 Swivel Yes

Electrical System


Driven with Constant Current Driver
 Input Voltage/Hz 220V- 240V/50-60Hz
 Control Gear Included
 Mounting Remote
 LED Power Watts 23.8W
 System Power Watts 27.4W
 Operating Voltage Vin 220-240 Vac
 Power Factor p.f. > 0.95

Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Spot On Framer ITA 85 Wide Beam	28W	WW27K	CR180	46°-56°	SBL	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Spot On Framer ITA 85 Wide Beam	28W	630	23	2700K WW27K	CR180	46°-56°	Black SBL	Non Dimmable On/Off
		658	24	3000K WW30K	CRI90			
		712	26	4000K NW40K				
		740	27	5700K CW57K				
Spot On Framer ITA 85 Wide Beam	28W			WW27K	CR180	46°-56°	SBL	On/Off



Light Distribution



LED Technology

Binning 3 Step MacAdam
 LED Life Time @ L70/B10 >50000 hours
 Colour Rendering (CRI) CR180, CR190
 Led Type COB
 LED Fitted Cree COB LED 36Vdc/700mA

Controls

Standard Switchable On/Off
 Optional Non Dimmable