

# Spot on Framer SR 45 | 9W

## Product Reference

Environment Indoor

Installation Semi Recess

## Construction & Materials

Housing Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish White,Black

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included




Mounting Remote

LED Power Watts 7.4W

System Power Watts 8.5W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 36Vdc/200mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Spot on Framer SR 45</b>	<b>9W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>22°-31°</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL	
<b>Spot on Framer SR 45</b>	<b>9W</b>	468	55	2700K <b>WW27K</b>	<b>CRI80</b>	22°-31°	White <b>SWH</b>	Non Dimmable	<b>On/Off</b>
		485	57	3000K <b>WW30K</b>	CRI90		Black <b>SBL</b>	Phase Dimmable	<b>PDIM</b>
		510	60	4000K <b>NW40K</b>				Dali Dimmable	<b>DDIM</b>
		519	61	5700K <b>CW57K</b>					
<b>Spot on Framer SR 45</b>	<b>9W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>22°-31°</b>	<b>SWH</b>	<b>On/Off</b>	