

# Spot on Framer SR 85

## Wide Beam | 24W

### Product Reference

Environment Indoor

Installation Semi Recess

### Construction & Materials

Housing Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish White,Black

Diffuser -

Antiglare Baffle -

### Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

### Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

### Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 19.6W

System Power Watts 22.5W

Operating Voltage Vin 220-240 Vac




Power Factor p.f. > 0.95

### Ordering Details

| Code Example: | Name                                  | Watt       | CCT          | CRI          | Angle          | Finish     | Control       |
|---------------|---------------------------------------|------------|--------------|--------------|----------------|------------|---------------|
|               | <b>Spot on Framer SR 85 Wide Beam</b> | <b>24W</b> | <b>WW27K</b> | <b>CRI80</b> | <b>46°-56°</b> | <b>SWH</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME                                  | WATT       | LUMEN | EFFICACY | CCT                | CRI          | ANGLE          | FINISH           | CONTROL                    |
|---------------------------------------|------------|-------|----------|--------------------|--------------|----------------|------------------|----------------------------|
| <b>Spot on Framer SR 85 Wide Beam</b> | <b>24W</b> | 540   | 24       | 2700K <b>WW27K</b> | <b>CRI80</b> | 46°-56°        | White <b>SWH</b> | Non Dimmable <b>On/Off</b> |
|                                       |            | 563   | 25       | 3000K <b>WW30K</b> | CRI90        |                | Black <b>SBL</b> | Phase Dimmable <b>PDIM</b> |
|                                       |            | 608   | 27       | 4000K <b>NW40K</b> |              |                |                  | Dali Dimmable <b>DDIM</b>  |
|                                       |            | 630   | 28       | 5700K <b>CW57K</b> |              |                |                  |                            |
| <b>Spot on Framer SR 85 Wide Beam</b> | <b>24W</b> |       |          | <b>WW27K</b>       | <b>CRI80</b> | <b>46°-56°</b> | <b>SWH</b>       | <b>On/Off</b>              |



### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 36Vdc/600mA

### Controls

Standard Switchable On/Off

Optional PDIM,DDIM,Non Dimmable