

Artlight ITA | 15W

Product Reference

Environment Indoor

Installation Track Mounted

Construction & Materials

Housing Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 12.5W


System Power Watts 14.4W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/350mA

Controls

Standard Switchable On/Off

Optional Non Dimmable

Ordering Details

| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|---------------------|------------|--------------|--------------|-------|------------|---------------|
| | Artlight ITA | 15W | WW27K | CRI80 | | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | CRI | ANGLE | FINISH | CONTROL |
|---------------------|------------|-------|----------|--------------|--------------|--------------|------------|----------------------------|
| Artlight ITA | 15W | 1440 | 100 | 2700K | WW27K | CRI80 | White | Non Dimmable On/Off |
| | | 1483 | 103 | 3000K | WW30K | | Black | |
| | | 1584 | 110 | 4000K | NW40K | | | |
| | | 1613 | 112 | 5700K | CW57K | | | |
| Artlight ITA | 15W | | | WW27K | CRI80 | | SWH | On/Off |