

Look Around SR | 10W

Product Reference

Environment Indoor

Installation Semi Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 8.8W




System Power Watts 10.1W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution

 $\eta = 100\%$

 $\eta = 100\%$

 $\eta = 100\%$


LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/250mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTDM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Look Around SR	10W	WW27K	CRI80	18°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE		FINISH		CONTROL	
Look Around SR	10W	970	96	2700K	WW27K	CRI80	18°(SS)	26°(MD)	White	SWH	Non Dimmable	On/Off
		1010	100	3000K	WW30K	CRI90	26°(MD)		Black	SBL	Phase Dimmable	PDIM
		1081	107	4000K	NW40K		36°(WD)		Custom	CSM	Dali Dimmable	DDIM
		1101	109	5700K	CW57K						Bluetooth Dimmable	BTDM
				2700K-5700K	TW						Casambi	CBTM
Look Around SR	10W			WW27K		CRI80	18°(SS)		SWH		On/Off	