

## Go Pro 35 AR | 5W

### Product Reference

Environment Indoor

Installation Ceiling Recess

### Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

### Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

### Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

### Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 3.4W




System Power Watts 4.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. &gt; 0.5



### Light Distribution



### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 &gt;50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/130mA

### Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable

### Ordering Details

| Code Example: | Name                | Watt      | CCT          | CRI          | Angle          | Finish     | Control       |
|---------------|---------------------|-----------|--------------|--------------|----------------|------------|---------------|
|               | <b>Go Pro 35 AR</b> | <b>5W</b> | <b>WW27K</b> | <b>CRI80</b> | <b>24°(MD)</b> | <b>SWH</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME                | WATT      | LUMEN | EFFICACY | CCT          |              | CRI          | ANGLE          | FINISH     |            | CONTROL        |               |
|---------------------|-----------|-------|----------|--------------|--------------|--------------|----------------|------------|------------|----------------|---------------|
| <b>Go Pro 35 AR</b> | <b>5W</b> | 420   | 100      | 2700K        | <b>WW27K</b> | <b>CRI80</b> | 24°(MD)        | White      | <b>SWH</b> | Non Dimmable   | <b>On/Off</b> |
|                     |           | 433   | 103      | 3000K        | <b>WW30K</b> | CRI90        | 36°(WD)        | Black      | <b>SBL</b> | Phase Dimmable | <b>PDIM</b>   |
|                     |           | 454   | 108      | 4000K        | <b>NW40K</b> |              | 52°(VWD)       |            |            | Dali Dimmable  | <b>DDIM</b>   |
|                     |           | 466   | 111      | 5700K        | <b>CW57K</b> |              |                |            |            | Casambi        | <b>CBTM</b>   |
|                     |           |       |          | Warm to Dim  |              |              |                |            |            |                |               |
| <b>Go Pro 35 AR</b> | <b>5W</b> |       |          | <b>WW27K</b> |              | <b>CRI80</b> | <b>24°(MD)</b> | <b>SWH</b> |            | <b>On/Off</b>  |               |