

Sigma 60 3-way | 3X8W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Aluminium

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Extruded Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 3x8.8W

System Power Watts 3x10.1W

Operating Voltage Vin 220-240Vac

Power Factor p.f. >0.95



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 33V-36Vdc/180mA

Controls

Standard Switchable On/Off

Optional DDIM

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Sigma 60 3-way	3x8W	WW27K	CRI80	29°(MD)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE		FINISH		CONTROL	
Sigma 60 3-way	3x8W	3x878	87	2700K	WW27K	CRI80	29°(MD)	29°(MD)	White	SWH	Non Dimmable	On/Off
		3x909	90	3000K	WW30K	CRI90	42°(WD)	42°(WD)	Black	SBL	Dali Dimmable	DDIM
		3x949	94	4000K	NW40K		62°(VWD)	62°(VWD)				
		3x969	96	5700K	CW57K							
Sigma 60 3-way	3x8W			WW27K		CRI80	29°(MD)		SWH		On/Off	