

Outline Wallgrazer 120 | 28W

Product Reference

Environment Outdoor

Installation Ceiling Surface

Construction & Materials

Housing Extruded Aluminium

Primary Lens Polycarbonate

Primary Reflector -

Secondary Reflector -

Body Finish Anodised Aluminium

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 23.1W


System Power Watts 26.6W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. >0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 34-36Vdc/700mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Outline Wallgrazer 120	28W	WW27K	CRI80	91°x30°	AL	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Outline Wallgrazer 120	28W	2846	107	2700K	WW27K	91°x30°	Anodised Aluminium	Non Dimmable
		2926	110	3000K	WW30K			Phase Dimmable
		3086	116	4000K	NW40K			Dali Dimmable
		3139	118	5700K	CW57K			Bluetooth Dimmable
				2700K-5700K	TW			Casambi
Outline Wallgrazer 120	28W			WW27K	CRI80	91°x30°	AL	On/Off

