

# iSoft Wash R 168 | 42W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Opal PC

Antiglare Baffle -

## Thermal Management

Heat Sink Material Extruded Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed Asymmetric

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 35.0W


System Power Watts 40.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 34-36Vdc/1050mA

## Controls

Standard Switchable On/Off

Optional DDIM,BTMM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>iSoft Wash R 168</b>	<b>42W</b>	<b>WW27K</b>	<b>CRI80</b>		<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>iSoft Wash R 168</b>	<b>42W</b>	2975	74	2700K <b>WW27K</b>	<b>CRI80</b>		White <b>SWH</b>	Non Dimmable <b>On/Off</b>
		3055	76	3000K <b>WW30K</b>	CRI90		Black <b>SBL</b>	Dali Dimmable <b>DDIM</b>
		3216	80	4000K <b>NW40K</b>			Custom <b>CSM</b>	Bluetooth Dimmable <b>BTMM</b>
		3296	82	5700K <b>CW57K</b>				Casambi <b>CBTM</b>
<b>iSoft Wash R 168</b>	<b>42W</b>			<b>WW27K</b>	<b>CRI80</b>		<b>SWH</b>	<b>On/Off</b>