

ZuG Dark S 168 | 50W

Product Reference

Environment Indoor

Installation Ceiling Surface

Construction & Materials

Housing Aluminium Extrusion

Primary Lens PMMA

Primary Reflector -

Secondary Reflector PC Black Cover

Body Finish White,Black

Diffuser -

Antiglare Baffle Black,White,Custom

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 42.8W


System Power Watts 49.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD high power

LED Fitted Osram/Cree 3030 LED array 39V-42Vdc/1050mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	ZuG Dark S 168	50W	WW27K	CRI80	28°(MD)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
ZuG Dark S 168	50W	5314	108	2700K	WW27K	CRI80	28°(MD) 28°(MD)	White SWH Non Dimmable On/Off
		5412	110	3000K	WW30K	CRI90	66°(VWD)	Black SBL Phase Dimmable PDIM
		5658	115	4000K	NW40K			Dali Dimmable DDIM
		5806	118	5700K	CW57K			Bluetooth Dimmable BTTM Casambi CBTM
ZuG Dark S 168	50W			WW27K	CRI80	28°(MD)	SWH	On/Off

