

Dark Knight 2 | 5W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector Black Raster – ABS

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included



Mounting Remote

LED Power Watts 4.4W

System Power Watts 5.5W


Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95




Light Distribution


η = 100%



η = 100%



η = 100%



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI90

Led Type SMD high power

LED Fitted -

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Dark Knight 2	5W	WW27K	CRI90	20°(ss)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL			
Dark Knight 2	5W	330	60	2700K	WW27K	CRI90	20°(SS)	White	SWH	Non Dimmable	On/Off
		341	62	3000K				Black		Phase Dimmable	
		369	67	4000K				Custom		Dali Dimmable	
		380	69	5700K				Custom		Dali Dimmable	
Dark Knight 2	5W			WW27K	CRI90	20°(SS)	SWH	On/Off			