

Tiny DR | 5W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Aluminium

Primary Lens Polycarbonate

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 3.4W

System Power Watts 4.2W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.5

Ordering Details


| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|----------------|-----------|--------------|--------------|----------------|------------|---------------|
| | Tiny DR | 5W | WW27K | CRI80 | 33°(MD) | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | CRI | ANGLE | FINISH | CONTROL |
|----------------|-----------|-------|----------|--------------|--------------|------------------------|------------|---|
| Tiny DR | 5W | 319 | 76 | 2700K | WW27K | CRI80 | 33°(MD) | White SWH Non Dimmable On/Off |
| | | 328 | 78 | 3000K | WW30K | CRI90 | 47°(WD) | Black SBL Phase Dimmable PDIM |
| | | 344 | 82 | 4000K | NW40K | | | Custom CSM DALI Dimmable DDIM |
| | | 353 | 84 | 5700K | CW57K | | | Casambi CBTM |
| | | | | | | Warm to Dim W2D | | |
| Tiny DR | 5W | | | WW27K | CRI80 | 33°(MD) | SWH | On/Off |



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/130mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable