

Linea Magic 48V 60 | 12.6W

Product Reference

Environment Indoor

Installation Track Mounted

Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish Black

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Voltage Driver

Input Voltage/Hz 48V

Control Gear Included



Mounting Remote

LED Power Watts 11.8W


System Power Watts -

Operating Voltage Vin 48V

Power Factor p.f. -



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 33V-36Vdc/350mA

Controls

Standard Switchable On/Off

Optional DDIM,BTDM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Linea Magic 48V 60	12.6W	WW27K	CRI80	112°	SBL	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH	CONTROL	
Linea Magic 48V 60	12.6W	861	73	2700K	WW27K	CRI80	112°	Black SBL	Non Dimmable	On/Off
		885	75	3000K	WW30K	CRI90			Dali Dimmable	DDIM
		932	79	4000K	NW40K				Bluetooth Dimmable	BTDM
		956	81	5700K	CW57K				Casambi	CBTM
				2700K-5700K	TW					
Linea Magic 48V 60	12.6W			WW27K		CRI80	112°	SBL	On/Off	

