

# Peeping Tom 48V | 2X4.5W

## Product Reference

Environment Indoor

Installation Track Mounted

## Construction & Materials

Housing Die Cast Aluminium, Milled Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White, Black

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

## Electrical System

Driven with Constant Voltage Driver

Input Voltage/Hz 48V

Control Gear Included


Mounting Remote

LED Power Watts 2X4.4W


System Power Watts -

Operating Voltage Vin 48V

Power Factor p.f. -



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80, CRI90

Led Type COB

LED Fitted Cree COB LED 9Vdc/500mA

## Controls

Standard Switchable On/Off

Optional DDIM, CASAMBI, Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Peeping Tom 48V</b>	<b>2X4.5W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>33°(MD)</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>Peeping Tom 48V</b>	<b>2X4.5W</b>	2x361	82	2700K	<b>WW27K</b>	<b>33°(MD)</b>	White	Non Dimmable
		2x374	85	3000K	<b>WW30K</b>		Black	Dali Dimmable
		2x387	88	4000K	<b>NW40K</b>			Casambi
		2x396	90	5700K	<b>CW57K</b>			
<b>Peeping Tom 48V</b>	<b>2X4.5W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>33°(MD)</b>	<b>SWH</b>	<b>On/Off</b>